

## Boilere Electrice cu Acumulare



Boilerele se monteaza vertical  
Sunt protejate prin acoperire ceramica la interior.  
Toate modelele sunt flansate si dotate cu anod de magneziu  
Presiune max. de lucru - 8 bar  
Isolatie: poliuretan de mare densitate CFC Free  
Sunt dotate cu supapa de siguranta

| MODEL          | VOLUM [l] | PUTERE [kW] | ALIMENTARE ELECTRICA | DIAMETRU [mm] | MASA [kg] |
|----------------|-----------|-------------|----------------------|---------------|-----------|
| CGA 1015RC     | 10        | 1.5         | 230V-50Hz            |               | 7.1       |
| CGU-1015RC     | 10        | 1.5         | 230V-50Hz            |               | 7.1       |
| CGA-1515RC     | 15        | 1.5         | 230V-50Hz            |               | 9.7       |
| GCU-1515RC     | 15        | 1.5         | 230V-50Hz            |               | 9.7       |
| GC 303612      | 30        | 1.2         | 230V-50Hz            | 360           | 13.8      |
| GC 503615      | 50        | 1,2         | 230V-50Hz            | 360           | 23        |
| GC 804515      | 80        | 1,5         | 230V-50Hz            | 450           | 28.7      |
| GC 1004515     | 100       | 1,5         | 230V-50Hz            | 450           | 31.9      |
| GCV 804720 P61 | 80        | 2           | 230V-50Hz            | 470           | 30        |

